

PIGMENT PASTES

Pigment Concentrates developed for ALCHIMICA's polyurethane products

DESCRIPTION

ALCHIMICA offers a wide range of pigment concentrates for the colouring of neutral or transparent versions of aliphatic topcoats, flooring systems and paints.

FEATURES & BENEFITS

At a maximum ratio of 10% by weight, the pigments are designed to be compatible with ALCHIMICA's products, offering high hiding power to any transparent or neutral polyurethane based waterproofing coating, flooring coating or paint.

RECOMMENDED FOR

The Pigment Pastes can be used for the colouring of any of ALCHIMICA's polyurethane coatings.

For example:

HYPERDESMO ADY-E (Neutral)
HYPERDESMO ADY-E (Transparent)
HYPERDESMO ADY-100 (Transparent)
HYPERDESMO ADY-2K (Neutral)
HYPERDESMO ADY-2K (Transparent)
HYPERDESMO-D (Transparent)
HYPERDESMO D-2K (Neutral)
HYPERFLOOR 2K (Neutral)
HYGROSMART PU CEMENT 3K

APPLICATION

1K Products: Pour the content of the pail into the product at a maximum ratio of 10% by weight. Mix thoroughly using a low-speed electric mixer until the product homogenizes. Apply the product as per standard application instructions.

2K Products: For 2 component products, the pigment paste should be added to the neutral component of each set at a maximum ratio of 10% by weight. Mix thoroughly using a low-speed electric mixer until the product homogenizes. Mix in the other component of the product and apply the product as per standard application instructions.

HYGROSMART PU CEMENT 3K: Mix the pigment at a maximum ratio of 10% as per the weight of Comp. B. Mix the pigment together with the whole set until the product homogenizes. Apply the product as per standard application instructions.


PACKAGING

1kg & 0.5kg pails

SHELF LIFE

12 months minimum in the original packaging when stored in dry places and at temperatures of 5-25°C.

NONE OF OUR PUBLISHED INSTRUCTIONS AND SPECIFICATIONS, IN WRITING OR OTHERWISE, ARE BINDING EITHER IN GENERAL OR WITH RESPECT TO ANY THIRD PARTY RIGHTS, OR DO THEY RELIEVE INTERESTED PARTIES OF THEIR DUTY TO SUBJECT THE PRODUCT TO AN ADEQUATE EXAMINATION OF ITS SUITABILITY. IN NO EVENT WILL ALCHIMICA S.A. BE RESPONSIBLE FOR DAMAGES OF ANY NATURE, WHATSOEVER, RESULTING FROM THE USE OF OR RELIANCE UPON INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS. ALCHIMICA S.A. RESERVES THE RIGHT TO CHANGE AT ANY TIME THE PROPERTIES OF ITS PRODUCTS. PLEASE REFER TO THE CURRENT VERSION OF THE TECHNICAL DATA SHEET, AVAILABLE FROM OUR WEB SITE WWW.ALCHIMICA.COM



Certified quality, environmental and occupational health & safety management systems:
ISO 9001/14001 & ISO 45001.

PIGMENT-PASTES/EE/27-01-2025