

FABRIC ROLL MAT WHITE

DESCRIPTION

Fabric Roll Mat is a non-woven, 100% polyester, needle punched.

RECOMMENDED FOR

Reinforcement of details, flashing, cracks and gaps. It is suitable for either solvent based or waterbased liquid waterproofing systems. It is particularly recommended for PU liquid membranes.

APPLICATION

Fabric Roll Mat is applied between the two coats of **HYPERDESMO**[®].

Application Conditions:

- Temperature: 5-35 °C.
- Relative humidity: < 85%.

PACKAGING

White: 100x200m rolls.

SHELF LIFE

Keep them in cool and dry places, at temperatures of 5-25 °C.

SAFETY INFORMATION

Fabric Roll Mat is not a hazardous material.

TECHNICAL CHARACTERISTICS

PROPERTY	UNITS	METHOD	SPECIFICATION
Weight	g/m ²	EN ISO 9864	45-55
Tensile strength	KN/m	EN ISO 10319	0.7-0.9
Thickness	mm	EN ISO 9863-1	0.65-1.05
Elongation at Break	%	EN ISO 10319	≥60

NONE OF OUR PUBLISHED INSTRUCTIONS AND SPECIFICATIONS, IN WRITING OR OTHERWISE, ARE BINDING EITHER IN GENERAL OR WITH RESPECT TO ANY THIRD PARTY RIGHTS, OR DO THEY RELIEVE INTERESTED PARTIES OF THEIR DUTY TO SUBJECT THE PRODUCT TO AN ADEQUATE EXAMINATION OF ITS SUITABILITY. IN NO EVENT WILL ALCHIMICA S.A. BE RESPONSIBLE FOR DAMAGES OF ANY NATURE, WHATSOEVER, RESULTING FROM THE USE OF OR RELIANCE UPON INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS. ALCHIMICA S.A. RESERVES THE RIGHT TO CHANGE AT ANY TIME THE PROPERTIES OF ITS PRODUCTS. PLEASE REFER TO THE CURRENT VERSION OF THE TECHNICAL DATA SHEET, AVAILABLE FROM OUR WEB SITE WWW.ALCHIMICA.COM

Certified quality, environmental and occupational health & safety management systems:
 ISO 9001/14001 & ISO 45001.

FABRIC ROLL MAT/EE/01-03-2016